

AIR-OPERATED GREASE PUMPS Mod. 660

COMPRESSION RATIO = 60:1

DELIVERY = 1600 g/min



Art. 020-1198-000

Double-acting air-operated oil pump Mod.605

ratio=5:1 Delivery capacity 28 l/min

For wall-fixing or fixed positions.

With additional accessories it allows to make different applications.

Polyurethane seals



010-1015-000	6,900	0,016	1
---------------------	-------	-------	---

Technical data 010-1015-000

Compression ratio		60:1
-------------------	--	------

Max pressure supply	bar	8
---------------------	-----	---

Medium air consumption	l/min	130
------------------------	-------	-----

Air inlet connection	BSP	F 1/4" G
----------------------	-----	----------

Grease outlet connection	BSP	M 1/4" G
--------------------------	-----	----------

Grease delivery capacity 8 barg/min		1600
-------------------------------------	--	------

Noise	dB	76
-------	----	----

Shank diameter	mm	30
----------------	----	----

Shank length	mm	950
--------------	----	-----

For drums with capacity of	kg	180-220
----------------------------	----	---------



These pumps are suitable for the supply at high pressure of greases with viscosity up to NLGI 2 at short and long distances. The operating pressure of the grease pumps hereby may vary between a minimum of 2.5 bar and a maximum of 8 bar. In order to optimize the efficiency and the life of our air-operated pumps, we recommend to use filtered and lubricated air.

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865

Sohar - 9133 2946, Salalah - 7193 6778

Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668,
9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opaltec.com Opal Tools & Equipment - Oman opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112,
Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com