

AIR-OPERATED OIL PUMPS Mod.605

COMPRESSION RATIO = 5:1
DELIVERY CAPACITY = 28 l/min



Art. 020-1198-000

Double-acting air-operated oil pump Mod.605
 ratio=5:1 Delivery capacity 28 l/min

For wall-fixing or fixed positions.

With additional accessories it allows to make different applications.

Polyurethane seals



020-1198-000	5,500	0,007	1
---------------------	-------	-------	---

Technical Data 020-1198-000

Compression ratio		5:1
Working pressure	bar	6-8
Air consumption	l/min	250
Air inlet connection	BSP	F 1/4" G
Oil outlet connection	BSP	M 1/2" G
Oil delivery capacity 8 bar	l/min	28
Noise	dB	80
Shank diameter	mm	42
Shank length	mm	215
For drums with capacity of	l	-



These pumps are advised for the transfer of medium-high viscosity oil (SAE 15/240), and anti-freeze, for medium-long distances (150 - 240 m). The delivery capacity of a pump varies according to particular applications and combinations: the pressure of air supplied; viscosity and temperature of the fluid; dimensions of delivery hose; dimensions of connections and type of gun which is used. The operating pressure may vary between a minimum of 3 bar and a maximum of 8 bar. The double-acting guarantees the delivery of a continuous and constant flow, suitable for installations on distribution facilities. To optimize the performance and the time-life of the air-operated pumps we advise to use filtered and lubricated air.

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865
 Sohar - 9133 2946, Salalah - 7193 6778
 Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973
 9983 3239, 9320 0399, 9897 5620, 9381 9668,
 9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opalte.com | Opal Tools & Equipment - Oman | opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112, Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com