

Our FRL range includes combination units with 1/4" and 1/2" inlet ports. Adding a PCL Air Treatment unit into an air line efficiently filters to 10 microns. Products feature polycarbonate bowls, allowing the user to easily monitor the element's condition and the collected liquid's level. The bowl is surrounded with protective metal as a safety measure to protect the user in case of excessive pressures, peratures, or aggressive chemicals.

FILTER - REGULATOR & LUBRICATOR

PCL's FRL Units are designed to control output air pressure, eliminate moisture and contaminants from the air flow, and to lubricate tools during use.

Features

- Selectable manual/semi-automatic drain
- Selectable manual/semi-automatic
- Locking device
- 10 micron filter
- Complete with wall bracket and
- pressure gauge



| Part Number | Port Size (in) | Adjustment | Max. Inlet Pressure | Flow @ 6 bar |
|-------------|----------------|------------------|---------------------|--------------|
| ATCFRL6 | 1/4 | 0-10 bar/145 psi | 12 bar | 1,800 l/min |

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865
Sohar - 9133 2946, Salalah - 7193 6778
Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668,
9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opalte.com | Opal Tools & Equipment - Oman | opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112,
Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com