

# T1300B

# JohnBean®

## PROVEN DESIGN FUNDAMENTAL VALUE

### TECHNICAL SPECIFICATIONS

Max Rim Diameter	22"   56cm
Max Tyre Width	13"   33cm
Max Wheel Diameter	39"   100cm
Power Supply	400V 3ph 50Hz 5,5A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	50"x68"x45"   125x173x115cm

## SWING-ARM TYRE CHANGER



### SWING-ARM

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.

### ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres

### TOP-SIDE BEAD SEATER

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.



### Showroom



#### Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

**Mabela Showroom:** 9396 6865

Sohar - 9133 2946, Salalah - 7193 6778

Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668,  
9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opalte.com | Opal Tools & Equipment - Oman | opaltoolsandequipment

### Head Office



#### Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112,  
Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com